

EX78900X Series

Hardened Managed 12-Port Gigabit PoE and 4-Port 10G SFP+ Ethernet Switch



Product Highlights

High Bandwidth and Versatility

- 12 10/100/1000BASE-T(X) ports for high bandwidth connections
- Up to 4 Dual-rate 1/10G SFP+ uplink ports for fiber connections
- Full capacity switching running at full duplex

Hardened-Grade for Non-Ventilated & Harsh Environments

- Wide operating temperature range -40 to 75°C (-40 to 167°F)
- Fanless operation
- High impact, thermal shock, and electrical noise resistance

Lite Layer 3 Functionality

- Static routing, RIP v1/v2, and OSPF
- Redundancy with VRRP
- Reduces amount of broadcast traffic

PoE Features

- IEEE 802.3bt with up to 90W per port; 360W total power budget
- PoE watchdog monitors status of connected PoE devices

Management/Security Features

- Port control, SFTP
- 802.1x port-based network access control and remote authentication through RADIUS
- Configure and monitor with eVue™ and eLite™

Support

- Complimentary technical support
- Free firmware upgrades and notifications
- Limited lifetime warranty

Overview

EtherWAN's EX78900X series is a hardened DIN-rail mounted managed PoE Ethernet switch platform. Equipped with up to 12 gigabit PoE ports along with 90W power and IEEE 802.3.bt protocol support and 4 dual-rate 10 gigabit SFP+ ports, the EX78900X series provides flexibility, speed, and reliability for networks in urban infrastructure, transportation, security, and other areas where connectivity is crucial.

Ordering Information

Model

EX78934X-0VB	12-port 10/100/1000BASE-T(X) PoE + 4-port 1/10G SFP+
---------------------	--

Software Features

Interface	+
CLI, Telnet, Web GUI, SSH	
Management	+
SFTP (Secured FTP) support	
Configuration backup	
DHCP Server/Client	
RMON (Remote Monitoring)	
Port Mirroring	
NTP (Network Time Protocol) synchronization	
PoE Watchdog	
LLDP (Link Layer Discovery Protocol)	
IPv4/IPv6	
SNMP v1/v2c/v3	
Security	+
MAC Address filtering	
Enable/Disable port	
Storm Control and Detection	
System logging	
IEEE 802.1x LAN Access Control	
Remote authentication through RADIUS and TACACS+	
Complex password support	
Multi-user login and privileged access management	
SSH for CLI and Telnet security	
TLS and HTTPS for web security	
ACL (Access Control List, up to 4096 entries)	
Quality of Service (QoS)	+
Priority Queues: 8 queues per port	
Traffic classification based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin), and strict mode	
Rate Limiting (Ingress/Egress)	


Layer 2 Features	+
Auto-negotiation for port speed and duplex	Flow Control IEEE 802.3x full duplex mode Back-pressure half duplex mode
Redundant Protocols	IEEE 802.1D STP IEEE 802.1w RSTP IEEE 802.1s MSTP EtherWAN's Alpha-Ring network fault recovery
VLANs	IEEE 802.1Q Tag VLANs GVRP GMRP
Link Aggregation	Static Trunk (4 groups) IEEE 802.3ad LACP
IGMP Snooping v1/v2/v3	
Layer 3 Features	+
IP Packet Routing	Maximum number of routes in hardware: 64 entries Static routing RIP v1/v2 OSPF v2
Routing Redundancy	VRRP
Software Properties and Performance	+
Switching Fabric	104Gbps
Forwarding Rate	75.29Mpps
Max VLANs	256 (4096 VID)
Jumbo Frame Size	9KB
MAC Table Size	16K
Packet Buffer Memory	12M bits

Hardware Specifications


Interface +	
Ethernet	12 x 10/100/1000BASE-T(X) 4 x 1/10G SFP+
Console	1 x RJ45
Config Backup	1 x USB (Type A Connector)
Digital Input	2 x Digital Input Wet Contact: 0-3V for State 0 13-30V for State 1 max input current: 8mA Dry Contact: Logic Level 1-Close to GND; Logic Level 0-Open
Alarm Contact	2 x Relay output, current capacity 0.5A/48VDC
LED Indicators	Per Unit: Power 1, Power 2 Per Port: Link/Activity (Green) Per PoE Port: PoE Status (Orange)
Technology +	
Standards	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX/100BASE-FX IEEE 802.3ab 1000BASE-T IEEE 802.3ad link aggregation control IEEE 802.3z 1000BASE-SX/1000BASE-LX IEEE 802.3x full duplex and flow control IEEE 802.1D STP IEEE 802.1p QoS IEEE 802.1Q Tag VLANs IEEE 802.1s MSTP IEEE 802.1w RSTP IEEE 802.1x PNAC IEEE 802.1ab LLDP IEEE 802.3az EEE IEEE 802.3af/at/bt Power over Ethernet
Forward/Filtering Rate	14,800pps for 10Mbps 148,810pps for 100Mbps 1,488,100pps for 1000Mbps 14,881,000pps for 10Gbps
Processing Type	Store-and-forward Auto-negotiation Half-duplex back-pressure and full-duplex flow control Auto MDI/MDIX
System Memory	2Gb DDR3 SDRAM
Flash Storage	1Gb
Power +	
Input	52-57VDC Redundant (Terminal block)
Power Consumption	20W Max (without PoE)
PoE Power Output	Ports 1-12: Up to 90W/port Power Budget: 360W
Protection	Reverse Polarity Protection

Physical +	
Casing Material	Aluminum
IP Rating	IP30
Dimensions	72 x 140 x 170mm (W x D x H) 2.8" x 5.5" x 6.7"
Weight	1.5kg (3.3lbs)
Installation Type	DIN-rail mounting
Environmental +	
Operating Temp.	-40 to 75°C (-40 to 167°F)
Storage Temp.	-45 to 85°C (-49 to 185°F)
Relative Humidity	5% to 95% (non-condensing)
Regulatory +	
ISO	Manufactured in ISO-9001 facility
EMI	FCC Part 15B Class A VCCI Class A EN 61000-6-4 EN 61000-3-2 EN 61000-3-3
EMS	EN 61000-4-2 (ESD) EN 61000-4-3 (Radiated RFI) EN 61000-4-4 (Burst) EN 61000-4-5 (Surge) PoE Ports: line to earth 6kV Surge EN 61000-4-6 (Induced RFI) EN 61000-4-8 (Magnetic field)
Safety	UL 61010
Traffic	NEMA TS2
Rail	EN 50121-4
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
Free Fall	FED STD 101C Method 5007.1
Warranty +	
Length	Limited Lifetime
Details	www.etherwan.com/support/warranty-policy
What's Included +	
Device	Ethernet switch
Cables	1 Console cable
Installation	Mounting brackets, screws
Documentation	Quick install guide

Dimensions



Application



Software

Network Management eVue™ Network Configuration and Monitoring Tool

Network Discovery eLite™ Network Discovery and IP Configuration Tool

EtherWAN [Home](#) [Devices](#) [Batch](#) [Group](#) [Events](#) [Settings](#) [Screen Zoom](#) [Logout](#)

Device List

IP	System Name	Group
192.168.50.12	EG99-5012	
192.168.50.62	EX709-5062	
192.168.50.254	R50	
192.168.50.11	EG99-5011	
192.168.50.63	EX74-5063	
192.168.50.14	EX779-5014	
192.168.50.61	EX71v2-5061	
192.168.50.44	EX71-5044	
192.168.50.64	EX73-5064	
192.168.50.34	EX739-5034	

Previous Page 1 of 3 Next

Topology

Online Offline Event

Latest Events

Acknowledged	ID	Severity	Time	Service	Node	Message
✓	5107	Normal	6/28/2019, 9:50:35 AM	login	server	User 'admin' logged in.
✓	5106	Normal	6/27/2019, 10:00:50 AM	login	server	User 'admin' logged in.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Web 192.168.1.19 is down.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Telnet 192.168.1.19 is down.
✓	5104	Normal	6/24/2019, 1:12:34 PM	login	server	User 'admin' logged in.

eLite — □ ×

List Server Firmware Configuration Help

IP Address	MAC Address	
192.168.50.22	00:e0:b3:50:22:00	
192.168.50.31	00:e0:b3:50:31:00	
192.168.50.72	00:e0:b3:50:72:00	
192.168.50.55	00:e0:b3:50:55:00	
192.168.50.23	00:e0:b3:50:23:00	
192.168.50.73	00:e0:b3:50:73:00	
192.168.50.44	00:e0:b3:50:44:00	
192.168.50.64	00:e0:b3:50:64:00	
192.168.50.43	00:e0:b3:50:43:00	
192.168.50.62	00:e0:b3:50:62:00	
192.168.50.71	00:e0:b3:50:71:00	
192.168.50.24	00:e0:b3:50:24:00	

Accessories

Hardened Gigabit & 10 Gigabit SFP Modules	+
www.etherwan.com/products/sfp-fiber-transceiver	
DIN-Rail Power Supplies	+
www.etherwan.com/products/din-rail-power-supply (*)	
*Recommended Power Supply	+
NDR-480-48 480W 48VDC DIN-Rail Power Supply	